

	<b>Product Name(s)</b>	Odelle Coloris Recessed 60 / 80 / 120 Cabinet with Aluminium Trim
	<b>Article Number(s)</b>	<b>60:</b> 70300 <b>80:</b> 70400 <b>120:</b> 70500
	<b>Product Description</b>	Recessed Cabinet with LED Front Illumination & Changeable Trim

<b>Net Weight (kg)</b>	<b>60:</b> 18.5kg <b>80:</b> 23.4kg <b>120:</b> 30kg
<b>Total Rated Wattage (w)</b>	<b>60:</b> 77w <b>80:</b> 79w <b>120:</b> 107w
<b>Lumens (lm)</b>	<b>60:</b> 2000lm <b>80:</b> 2200lm <b>120:</b> 2900lm
<b>Kelvins (k)</b>	6000k
<b>Light Source</b>	LED
<b>Energy Rating</b>	E
<b>IP Rating</b>	IP44
<b>Is the cabinet dimmable?</b>	NO
<b>Does product require an earth connection?</b>	YES
<b>Bypass sensor to work with main room light?</b>	NO
<b>Colour temperature change technology? CTC</b>	NO
<b>Heated pad only on when cabinet illuminated?</b>	YES
<b>How long is the warranty from date of purchase?</b>	<b>Silvering:</b> 5 Years <b>Electrical &amp; Other:</b> 2 Years

### Electrical Safety Information

hib. recommends that all electrical bathroom products should only be fitted by a suitably qualified, Part P registered electrician, in accordance with current IEE regulations. Ensure mains power supply is switched off before starting installation. Before drilling, ensure there are no hidden cables or pipes in the wall.

hib. recommend you receive the product before commencing with installation, as all sizes and measurements are approximate. hib. try and ensure all measurements are as accurate as possible. In the interest of continuous product development, hib. reserves the right to alter specification as necessary. E & OE